




Male Adapter

AMA



Connects Fractional Hn-Lok Port To Female NPT Thread

Part No.	Tube O.D. D		T* (NPT)	d (mm)	Width across flat h		L
	in	mm			in	mm	
AMA - 02T02N	1/8	3.17	1/8	2.03	7/16	11.11	29.50
AMA - 02T04N	1/8	3.17	1/4	2.03	9/16	14.28	34.80
AMA - 03T02N	3/16	4.76	1/8	3.04	7/16	11.11	30.22
AMA - 03T04N	3/16	4.76	1/4	3.04	9/16	14.28	35.56
AMA - 04T02N	1/4	6.35	1/8	4.32	7/16	11.11	31.80
AMA - 04T04N	1/4	6.35	1/4	4.32	9/16	14.28	37.08
AMA - 04T06N	1/4	6.35	3/8	4.32	11/16	17.46	37.84
AMA - 04T08N	1/4	6.35	1/2	4.32	7/8	22.22	43.43
AMA - 05T02N	5/16	7.93	1/8	4.57	7/16	11.11	32.76
AMA - 05T04N	5/16	7.93	1/4	5.59	9/16	14.28	38.10
AMA - 06T02N	3/8	9.52	1/8	4.83	7/16	11.11	33.50
AMA - 06T04N	3/8	9.52	1/4	6.86	9/16	14.28	38.90
AMA - 06T06N	3/8	9.52	3/8	6.86	11/16	17.46	39.60
AMA - 06T08N	3/8	9.52	1/2	6.86	7/8	22.22	45.20
AMA - 08T04N	1/2	12.70	1/4	7.11	9/16	14.28	44.50
AMA - 08T06N	1/2	12.70	3/8	9.40	11/16	17.46	45.20
AMA - 08T08N	1/2	12.70	1/2	9.40	7/8	22.22	50.80
AMA - 10T06N	5/8	15.87	3/8	9.50	11/16	17.46	47.40
AMA - 10T08N	5/8	15.87	1/2	11.94	7/8	22.22	52.30
AMA - 10T12N	5/8	15.87	3/4	12.70	1-1/16	26.98	52.30
AMA - 12T08N	3/4	19.05	1/2	11.94	7/8	22.22	52.30
AMA - 12T12N	3/4	19.05	3/4	14.73	1-1/16	26.98	52.30
AMA - 12T16N	3/4	19.05	1	14.73	1-3/8	34.92	57.91
AMA - 14T12N	7/8	22.22	3/4	15.75	1-1/16	26.98	54.80
AMA - 16T12N	1	25.40	3/4	15.75	1-1/16	26.98	58.70
AMA - 16T16N	1	25.40	1	20.32	1-3/8	34.92	66.00
AMA - 20T20N	1-1/4	31.75	1-1/4	25.91	1-3/4	44.45	80.26
AMA - 24T24N	1-1/2	38.10	1-1/2	31.75	2-1/8	53.97	94.48
AMA - 32T32N	2	50.80	2	43.69	2-9/16	65.09	119.38

* ISO Tapered Threads are available upon request.

Connects Metric Hn-Lok Port To Female ISO Taperad Thread

Part No.	Tube O.D. D	T* R(PT)	d Min.	Width across flat h	L
AMA - M06T02R	6	1/8	4.1	12	32.8
AMA - M06T04R	6	1/4	4.1	14	38.1
AMA - M08T04R	8	1/4	5.6	14	39.1
AMA - M10T04R	10	1/4	7.1	14	39.9
AMA - M10T06R	10	3/8	7.1	17	40.6
AMA - M10T08R	10	1/2	7.1	22	45.2
AMA - M12T04R	12	1/4	7.1	14	46.5
AMA - M12T06R	12	3/8	8.8	17	46.2
AMA - M12T08R	12	1/2	8.8	22	52.0
AMA - M18T08R	18	1/2	11.9	22	53.2
AMA - M18T12R	18	3/4	13.9	27	53.2
AMA - M28T16R	28	1	22.2	35	74.7
AMA - M28T20R	28	1-1/4	22.4	46	76.2
AMA - M32T20R	32	1-1/4	26.5	46	81.0
AMA - M38T24R	38	1-1/2	31.8	55	92.2

* NPT Threads are available upon request.